



## RO30xx DECORATIVE HYDRO OIL

Decoration-Protection-Maintenance

Field of application: furniture and complementary furnishings, inner doors, inner coverings, wood floorings.

**Information:** it protects and decorates the wood with design colours, which prevent any change of the natural aspect of the wood. Fast acting and easy to apply, it makes the wood highly water-repellent and smooth at the touch. All nuances of R030xx can be mixed between them to obtain new colours. To lighten a tone, it is necessary to cut the product with natural Decorative Oil RO3000. It is possible to apply a third coat of natural Decorative Oil to guarantee a higher protection.

## Instructions

Raw wood. Carefully clean the surface from dirt, oily marks, waxes and resins. Sand with 150-180 grit sandpaper and remove the powder. To maintain the colouring of the wood, apply 2-3 coats of natural Decorative Oil RO3000, at intervals of 1-2 hours. Between the coats, sand the surface with 320-400 grit sandpaper. To paint, apply two coats with a free-choice colour of R030xx range: apply the third coat of natural Decorative Oil R03000. if a higher protection is required. Between the coats, wait for 1-2 hours and sand with 320-400 grit sandpaper.

Coated wood. Sand with 80-150 grit sandpaper and remove the powder. Then proceed as indicated for the raw wood.

Maintenance: slightly sand with 220-320 grit sandpaper, remove the powder and apply one coat of the desired product, or eventually a brighter colour, which was cut with the transparent oil. On the most deteriorated parts, apply a second coat.

Overcoating: Decorative Oils R030xx range.

**Packaging:** 0,5 L, 2,5 L (only R03000, R03001, R03002)





R03004 **IRIDESCENT** CHARCOAL GREY



R03005 CHOCOLATE

R03001



R03002 IRIDESCENT DOVE GREY



R03006 CINNAMON



R03003 IRIDESCENT CLAY



R03007 BABY BLUF









Painting: at not less than 10°C



Ready to use



Application: by brush or cloth



Yield per coat: 12-24 m<sup>2</sup>/L



Mix it well before IISA



Drying time between Final drying time: the coats: 1-2 hours



5 hours



A+ certification