

RP4160 GLOSSY TOPCOAT

Protection-Finishing-Maintenance

Field of application: furniture and complementary furnishing, inner doors, tables, chairs, frames, skirting boards.

Information: this topcoat has an excellent transparency and a high wear resistance. RP4160 guarantees excellent wood protection. It is formulated with acrylic-polyurethane resins and it is low in solvents, it does not contain substances that can create health problems to the user and to the environment.

Instructions

Raw wood. Sand with 180-220 grit sandpaper and remove the powder. To maintain the natural colour of the wood, apply 2-3 coats of RP4160 glossy Topcoat at an interval of 2-4 hours. To coat, apply a coat of RMxx10 Impregnating stain or RGxx80 Gel Impregnating stain; wait for 3 hours, then apply 2-3 coats of RP4160 glossy Topcoat at an interval of 2-4 hours.

Coated wood. Sand with 80-150 grit sandpaper and remove the powder. Then, proceed as indicated for the raw wood.

Overcoating: Glossy Topcoat RP4160.

Packaging: 0,75 L.



Storage: at not less than 5°C



Painting: at not less than 10°C



Ready to use



Application: by brush or spray gun



Yield per coat: 10 m²/L



Mix it well before use



Drying time between the coats: 2-4 hours



Final drying time: 24 hours



A+ certification



RP4160
 TRANSPARENT