



RB2x70 FLOOR PRESTIGE

High resistance coatings for floorings

Field of application: ceramic, stoneware, stone, concrete, cotto tiles and wood floorings.

Information: Floor Prestige is the high-tech, 1k matt coating for the renovation of floorings. Extremely resistant to foot traffic and abrasion, it is also suitable for surfaces with high traffic. Its water-based formula is odourless and with low VOC emissions, making this coating suitable for indoor spaces. Floor Prestige is a washable and high-covering product that strongly adheres to all kinds of surfaces carefully cleaned. In case of surfaces already coated, it is necessary to evaluate if a slight sanding of the old coating layer is necessary.

No primer application required.

Suitable for spaces, subject to HACCP standard.

The product is certified and complies with UNI 11021:2002 standard.

Instructions

Clean the surface from dust and grease that could avoid the adhesion of the coating. Do not apply over floorings, treated with oils, waxes or derivatives. Apply the product over the surface. Let it dry off (drying time between coats: min. 2 hours) before the application of the second coat. Two or three coats are recommended on surfaces subject to foot traffic. Ventilate the room after applying the product. On surfaces subject to wear, Floor Prestige can be protected with matt Topcoat for wood floorings RP2260.

Overcoating: Floor Prestige can be protected with matt Topcoat for wood floorings RP2260.

Packaging: 0,75 L, 2,5 L.



Storage: at not less than 5°C



Painting: at not less than 10°C



Ready to use



Application: by brush, spray gun or roller



Yield per coat: 14 m² / L



Mix it well before use



Drying time between the coats: 2 hours



Final drying time: 24 hours



RB 2070
DOVE GREY



RB 2170
PAPYRUS



RB 2270
CONCRETE



RB 2370
LEAD



RB 2470
CHARCOAL GREY