



RPxx60 FLOORINGS AND FURNITURE TOPCOAT

Maintenance-Finishing for wood floorings and furniture

Field of application: wood floorings and furniture.

Information: it is a topcoat for wood floorings with great transparency and a great resistance to foot traffic abrasion. It is formulated with acrylic-polyurethane resins, it is extremely resistant to wear, elastic, low in solvents and it does not contain substances that can create health problems to the user and to the environment. It does not turn yellowish, thanks to its special UV filters, which also allow a fair protection of the natural colour of the wood.

Instructions

Unused floor: sand the raw wood with 150 grit sandpaper and remove the powder. Apply 3 coats of RPxx60 at an interval of 2-4 hours. It is not necessary to sand between the coats. To increase the performances, apply one coat of RP1060 Grain Filler and 2 coats of RPxx60 Topcoat.

Coated floor: on a paint finish which is in good condition, sand with 240-280 grit sandpaper. Clean the surface, then proceed to paint. On a paint finish which is in bad condition sand with 80-150 grit sandpaper to bring the wood back to the raw condition. Clean the surface and proceed to paint as indicated for the unused wood.

Overcoating: Floorings and furniture topcoats RPxx60.

Packaging: 0,75 L, 2,5 L.



Storage at not less than 5°C



Painting at not less than 10°C



Ready to use



Application by brush, spray gun or roller



Yield per coat
10 m²/L



Mix it well
before use



Drying time between
the coats 2-4 hours



Final drying time
24 hours



RP1160
SEMI-GLOSSY
TRANSPARENT



RP2260
MATT
TRANSPARENT